

FITTINGS SEGMENTADO PARA TUBERIA DE HDPE



TEE

Tee 90° según DIN 16963

Diámetro (d)	L1	L2
* 90	400	200
110	410	205
125	430	215
140	440	220
160	460	230
180	480	240
200	500	250
225	530	265
250	750	375
280	780	390
315	920	460
355	960	480
400	1000	500
450	1050	525
500	1200	600
560	1260	630
630	1330	665
710	1410	705
800	1500	750
900	1700	850
1000	1800	900
1200	2000	1000

* De acuerdo a normas internas.

CODO

Codos 90° 4 segmentos $r=dx1,5$ según DIN 16963

Diámetro (d)	Radio (R)	Z	L1=L2	L3=L4
* 90	135	150	90	136
110	165	315	156	262
125	188	338	178	270
140	210	360	200	290
160	240	390	230	310
180	270	420	180	270
200	300	450	200	275
225	338	488	225	300
250	375	625	250	410
280	420	670	280	430
315	473	773	315	510
355	533	833	355	535
400	600	900	400	555
450	675	975	450	590
500	750	1100	500	670
560	840	1190	560	690
630	945	1295	630	770
710	1065	1415	710	810
800	1200	1550	800	830
900	1350	1750	900	NA
1000	1500	1900	1000	NA
1200	1800	1900	1200	NA

* De acuerdo a normas internas.

Notas:

- Información técnica de Tee y Codos de 45° y 60°, solicítela a su vendedor o en www.attconexiones.cl
- Dimensiones de fittings de 1200 mm. a 2000 mm., consultarlas a nuestro departamento técnico.

